

Part-No.: HPL22DS-1

Product Specification	
Battery Size:	4*AA
Light Source:	Cree XP-G LED
IP-Rating:	IP68 (3m)
Mode:	High / Low / Flash / Off

Mechanical Data	
Dimensions:	172 mm x 47 mm x 47 mm (L X W X D)
Weight:	140 g

Technical Data	
Light Output:	62 lm (Mode Low) ~ 157 lm (Mode High)
Beam Distance:	83 m (Mode Low) ~ 117 m (Mode High)
Run Time:	13 hrs (Mode Low) ~ 6hrs 10 min (Mode High)

Certification & Standards	
UL	CLASS I DIV 1 GRP ABCD CLASS II DIV 1 GRP EFG CLASS III TEMP CODE: T4
ATEX	Ⓔ II 1 G Ex ia IIC T4 IP67
IECEX	Ex ia IIC T4 Ga IP67
MSHA	APPROVAL No. 20-A150004-0 (Tested for intrinsic safety in Methane-air mixtures only)
CE	Approved
ROHS	Approved
REACH	Approved

#### Intrinsically Safe Flashlight for Use in Hazardous Environments



#### Accessories



HPL22140



HPL22001203

CR20160524TP-D-22-HPL22DS1

## Product Specification